

LABELMATE USA

Label Handling Innovations

REEL-TO-REEL REWINDERS

The new off-line **RRR-330** and **RRR-330-A Reel-to-Reel Unwinders / Rewinders** provide a convenient way to reverse the wind direction of your label roll (Wind-In / Wind-Out) in a self-contained table-top package.

Designed for all-day, every-day use, these **Reel-to-Reel Unwinders / Rewinders** are backed by a 3-Year Parts and Labor Limited Warranty, assuring you reliable performance.



RRR-330
HWD: 13" x 32.5" x 13"
(330-mm x 826-mm x 330-mm)

CONTROLS

- Power On-Off
- Stop / Run
- Speed Adjust
- Speed Variable/Maximum
- Photocell Sensitivity Adjust
- New Bi-directional rewind capability!



RRR-330-A
HWD: 13" x 32.5" x 13"
(330-mm x 826-mm x 330-mm)

KEY FEATURES & BENEFITS

- "Wind-In" or "Wind-Out" to reverse the facing direction of labels.
- Uni-directional Rewind to the right-hand Spindle. The left-hand Spindle is the Unwind (supply) Spindle.
- Auto-Stop at end of roll.
- Label width: Up to 6" (152-mm). Adjustable Label Guide helps realign uneven label rolls.
- Rugged Construction. Universal 100-240V 50-60Hz Power Supply.
- Rewind speed varies with roll diameter.
- Standard 3" (76-mm) Fin-style Unwind Core Holder.

REWIND CORE	UNWIND CORE	ROLL DIA.	SPEED	REEL-to-REEL UNWIND / REWIND SYSTEMS	MODEL
3" (76-mm)	3" (76-mm)	13" (330-mm)	Up to 92"/sec.	As above with 13" (330-mm) Roll Diameter capacity.	RRR-330
1" - 4" adjustable	3" (76-mm)	13" (330-mm)		As above with 13" (330-mm) Roll Diameter capacity. and a 1" to 4" Adjustable Rewind Core Holder.	RRR-330-A
OPTIONS FOR RRR UNWIND/REWIND SYSTEMS					
Extra Unwind Shaft for 1" Cores. Change from the standard 3" Core Holder in minutes.					RR-1"U
Extra Unwind Shaft for 1.5" Cores. Change from the standard 3" Core Holder in minutes.					RR-1.5"U
Extra Unwind Shaft for 40-mm Cores. Change from the standard 3" Core Holder in minutes.					RR-40mmU