

Datamark Solvent DOD Porous J100

Datamark Identification

Chemwatch: 50612 Version No: 6.1.1.1

Material Safety Data Sheet according to NOHSC and ADG requirements

Chemwatch Hazard Alert Code: 2

Issue Date: 07/04/2014 Print Date: 10/07/2014 Initial Date: Not Available S.Local.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier	
Product name	Datamark Solvent DOD Porous J100
Chemical Name	Not Applicable
Synonyms	31300103 cleaning solvent
Proper shipping name	Not Applicable
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Used for viscosity control, washdown, purging with use of DOD Porous Ink Jet Systems.

Details of the manufacturer/importer

Registered company name	Datamark Identification
Address	19 Lang Parade QLD 4064 Milton Australia
Telephone	1300 657 633
Fax	+61 7 3271 2751
Website	Not Available
Email	Not Available

Emergency telephone number

. J			
Association / Organisation	Not Available		
Emergency telephone numbers	0414 373 494		
Other emergency telephone numbers	0414 373 494	1 1 1	I I I

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

Poisons Schedule	S6		
Risk Phrases ^[1]	R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.	
	R36/38	Irritating to eyes and skin.	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI		
GHS Classification [1]	Acute Toxicity (Oral) Category 4, Acute Toxicity (Dermal) Category 4, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 2, Eye Irrit. 2		
Legend:	Classified by Chemwatch	n; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI	

Label elements

GHS label elements



SIGNAL WORD

WARNING

Issue Date: **07/04/2014**Print Date: **10/07/2014**

Hazard statement(s)

H302	Harmful if swallowed
H312	Harmful in contact with skin
H332	Harmful if inhaled
H315	Causes skin irritation
H319	Causes serious eye irritation

Supplementary statement(s)

Not Applicable

CLP classification (additional)

Not Applicable

Precautionary statement(s): Prevention

P271	Use only outdoors or in a well-ventilated area.	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P270	Do not eat, drink or smoke when using this product.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	

Precautionary statement(s): Response

P321	Specific treatment (see advice on this label).	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.	

Precautionary statement(s): Storage

Not Applicable

Precautionary statement(s): Disposal

P501 Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration

Label elements



Other hazards

Relevant risk statements are found in section 2

Indication(s) of danger Xi

SAFETY ADVICE	
S07	Keep container tightly closed.
S09	Keep container in a well ventilated place.
S13	Keep away from food, drink and animal feeding stuffs.
S23	Do not breathe gas/fumes/vapour/spray.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
S36	Wear suitable protective clothing.
S37	Wear suitable gloves.
S39	Wear eye/face protection.
S40	To clean the floor and all objects contaminated by this material, use water.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well ventilated areas.
S56	Dispose of this material and its container at hazardous or special waste collection point.
S64	If swallowed, rinse mouth with water (only if the person is conscious).

Limited evidence of a carcinogenic effect*.

Cumulative effects may result following exposure*.

Vapours potentially cause drowsiness and dizziness*.

May possibly affect fertility*.

Datamark Solvent DOD Porous J100

Issue Date: **07/04/2014**Print Date: **10/07/2014**

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	
111-76-2	10-30	ethylene glycol monobutyl ether	
7732-18-5	>60	<u>water</u>	
	NotSpec.	NOTE: Manufacturer has supplied full ingredient	
	NotSpec.	information to allow CHEMWATCH assessment.	

NOTE: Manufacturer has supplied full ingredient information to allow CHEMWATCH assessment.

SECTION 4 FIRST AID MEASURES

Description of first aid measures

bescription or mot ala measures	
Eye Contact	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Followed acute or short term repeated exposures to ethylene glycol monoalkyl ethers and their acetates:

- ▶ Hepatic metabolism produces ethylene glycol as a metabolite.
- ▶ Clinical presentation, following severe intoxication, resembles that of ethylene glycol exposures.
- ▶ Monitoring the urinary excretion of the alkoxyacetic acid metabolites may be a useful indication of exposure.

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

▶ foam.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Advice for firefighters

Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.

Version No: **6.1.1.1**

Datamark Solvent DOD Porous J100

Issue Date: **07/04/2014**Print Date: **10/07/2014**

Fire/Explosion Hazard

- ▶ The material is not readily combustible under normal conditions
- ▶ However, it will break down under fire conditions and the organic component may burn.
- Not considered to be a significant fire risk.
- ▶ Heat may cause expansion or decomposition with violent rupture of containers.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- ▶ Control personal contact with the substance, by using protective equipment.
- ▶ Contain and absorb spill with sand, earth, inert material or vermiculite.

Moderate hazard. • Clear area of

- Major Spills
- ▶ Clear area of personnel and move upwind.
- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

- ▶ DO NOT allow clothing wet with material to stay in contact with skin
- ▶ Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

Other information

- Store in original containers.
- ▶ Keep containers securely sealed.
- ▶ Store in a cool, dry, well-ventilated area.
- ▶ Store away from incompatible materials and foodstuff containers.

Conditions for safe storage, including any incompatibilities

Suitable container

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
 Check all containers are clearly labelled and free from leaks.

Storage incompatibility

None known













- X Must not be stored together
- May be stored together with specific preventions
- May be stored together
 May be stored together

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	ethylene glycol monobutyl ether	2-Butoxyethanol	96.9 mg/m3 / 20 ppm	242 mg/m3 / 50 ppm	Not Available	Sk

EMERGENCY LIMITS

Ingredient	TEEL-0	TEEL-1	TEEL-2	TEEL-3
ethylene glycol monobutyl ether	50 ppm	50 ppm	100 ppm	700 ppm
water	500 ppm	500 ppm	500 ppm	500 ppm

Ingredient	Original IDLH	Revised IDLH
ethylene glycol monobutyl ether	700 ppm	700 [Unch] ppm
water	Not Available	Not Available

Issue Date: **07/04/2014**Print Date: **10/07/2014**

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Personal protection











Eye and face protection

- Safety glasses with side shields.
- Chemical goggles
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when

making a final choice.

Body protection

See Other protection below

Other protection

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Thermal hazards

Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-*

Datamark Solvent DOD Porous J100

Material	СРІ
BUTYL	Α
NEOPRENE	Α
##ethylene glycol monobutyl	ether

^{*} CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	A-AUS / Class 1	-	A-PAPR-AUS / Class 1
up to 25 x ES	Air-line*	A-2	A-PAPR-2
up to 50 x ES	-	A-3	-
50+ x ES	-	Air-line**	-

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

• •	• •		
Appearance	Liquid with a low odour; miscible with water.		
Physical state	Liquid	Relative density (Water = 1)	0.95
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available

Datamark Solvent DOD Porous J100

Issue Date: **07/04/2014**Print Date: **10/07/2014**

Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution(1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo. Ethylene glycol monobutyl ether (2-butoxyethanol) and its metabolite butoxyacetic acid are haemolytic agents, causing red blood cell destruction. On the basis of industrial experience and volunteer short-term exposure humans are shown to be less susceptible than experimental animals to exposure.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may product serious damage to the health of the individual. Severe acute exposure to ethylene glycol monobutyl ether, by ingestion, may cause kidney damage, haemoglobinuria, (blood in urine) and is potentially fatal.
Skin Contact	Skin contact with the material may be harmful; systemic effects may result following absorption. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Ethylene glycol monobutyl ether (2-butoxyethanol) penetrates the skin easily and toxic effects via this route may be more likely than by inhalation. Percutaneous uptake rate in the guinea pig was estimated to be 0.25 umole/min/cm2. The material produces mild skin irritation; evidence exists, or practical experience predicts, that the material either produces mild inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant, but mild, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.
Еуе	When instilled in rabbit eyes ethylene glycol monobutyl ether produced pain, conjunctival irritation, and transient comeal injury. Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.
Chronic	Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. There is some evidence that human exposure to the material may result in developmental toxicity. This evidence is based on animal studies when effects have been observed in the absence of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not secondary non-specific consequences of the other toxic effects. Exposure to the material may cause concerns for human fertility, on the basis that similar materials provide some evidence of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects, but which are not a secondary non-specific consequence of other toxic effects.

Datamark Solvent DOD Porous J100	TOXICITY	IRRITATION
	Not Available	Not Available
	TOXICITY	IRRITATION
	Dermal (Guinea pig) LD50: 210 mg/kg **	* [Union Carbide]
ethylene glycol monobutyl ether	Dermal (rabbit) LD50: 220 mg/kg	Eye (rabbit): 100 mg SEVERE
entylene grycor monobatyr enter	Inhalation (Rat) LC50: 2210 mg/m3 **	Eye (rabbit): 100 mg/24h-moderate
	Inhalation (Rat) LC50: 450 ppm *	Skin (rabbit): 500 mg, open; mild
	Oral (Rat) LD50: 300 mg/kg **	

Chemwatch: **50612** Page **7** of **8** Issue Date: **07/04/2014**Version No: **6.1.1.1** Print Date: **10/07/2014**

Datamark Solvent DOD Porous J100

	Oral (rat) LD50: 470 mg/kg Not Available	Not Available
water	TOXICITY Not Available	IRRITATION Not Available

^{*} Value obtained from manufacturer's msds

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

No significant acute toxicological data identified in literature search. For ethylene glycol monoalkyl ethers and their acetates (EGMAEs): Typical members of this category are ethylene glycol propylene ether (EGPE), ethylene glycol butyl ether (EGBE) and ethylene glycol hexyl **Datamark Solvent DOD Porous J100** ether (EGHE) and their acetates. EGMAEs are substrates for alcohol dehydrogenase isozyme ADH-3, which catalyzes the conversion of their terminal alcohols to aldehydes (which are transient metabolites). Further, rapid conversion of the aldehydes by aldehyde dehydrogenase produces alkoxyacetic acids, which are the predominant urinary metabolites of mono substituted glycol ethers. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis ETHYLENE GLYCOL MONOBUTYL The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of **ETHER** dermatitis is often characterised by skin redness (erythema) and swelling epidermis. NOTE: Changes in kidney, liver, spleen and lungs are observed in animals exposed to high concentrations of this substance by all routes. ** ASCC (NZ) SDS WATER No significant acute toxicological data identified in literature search. **Acute Toxicity** 0 Carcinogenicity 0 Skin Irritation/Corrosion Reproductivity · 0 Serious Eye Damage/Irritation STOT - Single Exposure STOT - Repeated Exposure 0 Respiratory or Skin sensitisation 0 0 0 Mutagenicity **Aspiration Hazard**

Legend:

— Data required to make classification available

X – Data available but does not fill the criteria for classification

O – Data Not Available to make classification

CMR STATUS

SKIN	ethylene glycol monobutyl ether	Australia Exposure Standards - Skin	Sk
	, , ,	·	

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

For ethylene glycol monoalkyl ethers and their acetates:

Members of this category include ethylene glycol propyl ether (EGPE), ethylene glycol butyl ether (EGBE) and ethylene glycol hexyl ether (EGHE)

Environmental fate

The ethers, like other simple glycol ethers possess no functional groups that are readily subject to hydrolysis in the presence of waters. The acetates possess an ester group that hydrolyses in neutral ambient water under abiotic conditions.

Level III fugacity modeling indicates that category members, when released to air and water, will partition predominately to water and, to a lesser extent, to air and soil. Estimates of soil and sediment partition coefficients (Kocs ranging from 1- 10) suggest that category members would exhibit high soil mobility.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Not Available	Not Available	Not Available

Bioaccumulative potential

Ing	redient	Bioaccumulation
Not	Available	Not Available

Mobility in soil

mobility in 301		
	Ingredient	Mobility
	Not Available	Not Available

SECTION 13 DISPOSAL CONSIDERATIONS

Issue Date: **07/04/2014**Print Date: **10/07/2014**

Product / Packaging disposal

- ► Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

ethylene glycol monobutyl ether(111-76-2) is found on the following regulatory lists

"IOFI Global Reference List of Chemically Defined Substances", "International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "Australia Exposure Standards", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards","IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances","Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Inventory of Chemical Substances (AICS)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix I". "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)","Australia National Pollutant $Inventory", "OECD\ Existing\ Chemicals\ Database", "Sigma-Aldrich Transport\ Information", "Australia\ High\ Volume\ Industrial\ Chemical\ List\ Transport\ December 1997, and the property of the property$ (HVICL)","United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)","Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Appendix E (Part 2)", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "International Air Transport Association (IATA) Dangerous Goods Regulations","Australia Hazardous Substances Information System - Consolidated Lists","International Fragrance Association (IFRA) Survey: Transparency List","IMO IBC Code Chapter 17: Summary of minimum requirements","Acros Transport Information","Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6"

water(7732-18-5) is found on the following regulatory lists

"OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution – Norway", "WHO Model List of Essential Medicines - Adults", "Australia Inventory of Chemical Substances (AICS)", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "Sigma-AldrichTransport Information", "Australia High Volume Industrial Chemical List (HVICL)", "International Fragrance Association (IFRA) Survey: Transparency List"

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.